


AGM JUMP STARTER

PROPULSTATION ⚡ 12/24V ⚙️ 2400/1200 CA



+++

Robust shell case design 5 mm shatterproof polyethylene

Long and flexible cables with a double insulation

The battery has exceptionally high capacity to accumulate and disperse high-amperage energy

Fully insulated clamps

LED system indicates the voltage to select on the booster

LED light ON if the booster is correctly connected to the station

The contactor ensures an optimal recharge of the booster (5 magnetic poles)

The 500 A fuse is directly accessible from the outside of the booster



500A

THE PROPULSTATION RANGE



PPS 12V
800 CA



PPS 12V
1200 CA



PPS 12/24V
2400/1200 CA



PPS 12V
6400 CA



PPS 12/24V
3200/1600 CA



PPS 24V
3200 CA

TECHNICAL INFORMATION

MODEL	PPS 12V 800	PPS 12V 1200	PPS 12/24V 2400/1200 CA	PPS 12V 6400 CA	PPS 12/24V 3200/1600 CA	PPS 24V 3200 CA
PART NUMBER	521002	520003	520008	560004	560000	560003
VOLTAGE (DC)	12V	12V	12/24V	12V	12/24V	24V
CRANKING AMPS (CA)	800 A	1200 A	2400/1200 A	6400 A	3200/1600 A	3200 A
CABLE LENGTH	1,55 m	1,55 m	1,35 m	2,10 m	2,10 m	2,10 m
CABLE CROSS SECTION	35 mm ²	50 mm ²	50 mm ²	70 mm ²	70 mm ²	70 mm ²



PACKAGING INFORMATION

MODEL	PPS 12V800	PPS 12V1200	PPS 12/24V 2400/1200 CA	PPS 12V 6400 CA	PPS 12/24V 3200/1600 CA	PPS 24V 3200 CA
NET WEIGHT	13,55 kg	17,50 kg	27,90 kg	75 kg	70 kg	70 kg
DIMENSIONS (L x W x H / mm)	450 x 170 x 510	450 x 170 x 510	560 x 190 x 610	580 x 510 x 1100	580 x 510 x 1100	580 x 510 x 1100

HOW TO CHOOSE

PART NUMBER	MODEL	VOLTAGE	12V								24V							
			<125*	150	175	250	300	350	500	1000+	100	250	500	1000	1500	2000		
			HP* = CHECK YOUR ENGINE HP - LEGEND:										NORMAL		INTENSIVE			
521002	PPS 800	12V	■	■	■	■												
520003	PPS 1200	12V	■	■	■	■	■	■										
520008	PPS 2400/1200	12/24V	■	■	■	■	■	■	■	■		■	■	■	■	■		
560004	PPS 6400	12V	■	■	■	■	■	■	■	■	■							
560000	PPS 3200/1600	12/24V	■	■	■	■	■	■	■	■	■	■	■	■	■			
560003	PPS 3200	24V										■	■	■	■	■		

RELATED PART NUMBER:

DOCKING STATION

	DC Vehicle station - with DC cable
	AC Workshop station - with charger AC/DC-230/12V

BATTERY CHARGER FOR DOCKING STATION AC

	PPS 12V	PPS 12/24V	12V Mobile	12/24V Mobile	24V Mobile
	AC12	AC1224	ACM	ACM	ACM
	DC12	DC1224	DCM	DCM	DCM
	12V-2 A PN: 522502	12V-4 A PN: 522504	12V-10 A PN: 522510	12V-7 A PN: 522507	12V-10 A PN: 845120-A



Rue de la Baronnerie, 3
4920 Harzé - Belgium

+32 4 388 20 17

info@schumachereurope.com
www.schumachereurope.com

@schumacherboosters

Since
1947

#passionatesince1947